







110 x 540mm Rhomboid 53028 (matt)



Technical Specification

Properties		Test Method	Required Value	Value	
	Water absorption	ISO 10545-3	≥ 0.5%	≥ 0.5%	
	Determination of dimensions	ISO 10545-2	Length and width ± 0.6% Thickness ± 5.00% Edge straightness ± 0.5% Surface flatness ± 0.5%	Length and width ± 0.6% Thickness ± 5.00% Edge straightness ± 0.5% Surface flatness ± 0.5%	
o v	Breaking strength	ISO 10545-4	Min. 1300 N	≤1300 N	
o v	Modulus of rupture	ISO 10545-4	Min. 32 N/mm²	≥ 35 N/mm²	
N. C.	Slip resistance (oil wet ramp test)	DIN 51130 B.G.R. 181"	N/A	R9	
	Chemical resistance	ISO 10545-13	Min. UB	A, LA, HA	
	Stain resistance	ISO 10545-14	Min class 3	Class 5	
	Origin	N/A	N/A	ltaly	
	Shade variation	N/A	N/A	V4	
1 2 3 4 5 6 7 8 9	Number of faces	N/A	N/A	46	



Packing Information

Tile description		Quantity per box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
110 x 540 x 9mm Rhomboid	Matt	18	19.09	20.18 kg	42.44	45



The data and information contained in these specification sheets are indicative only unless stated otherwise.

As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation.

The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose.

To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.

No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

