





Palazzo



PALAZZO

COLOURS, FORMATS & FINISHES


					
In/Out P4	White	Cream	Light Grey	Dark Grey	Charcoal
600 x 1200mm	●	●	●	●	●
600 x 600mm	●	●	●	●	●
600 x 600m	●	●	●	●	●
300 x 600mm	●	●	●	●	●
300 x 300mm	●	●	●	●	●
Textured P5					
600 x 600mm	●	●	●	●	●

FINISH: **IN/OUT** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V3
FINISH: **TEXTURED** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V3






600 x 600mm
53984 (in/out)
54405 (textured 2CM)





600 x 1200mm
53979 (in/out)




300 x 300mm
53994 (in/out)




300 x 600mm
53989 (in/out)




600 x 600mm
53985 (in/out)
54402 (textured 2CM)



600 x 1200mm
53980 (in/out)



300 x 300mm
53995 (in/out)



300 x 600mm
53990 (in/out)




Light Grey



600 x 600mm
53986 (in/out)
54403 (textured 2CM)




600 x 1200mm
53981 (in/out)



300 x 300mm
53996 (in/out)



300 x 600mm
53991 (in/out)



Dark Grey



600 x 600mm
53987 (in/out)
54404 (textured 2CM)



600 x 1200mm
53982 (in/out)



300 x 300mm
53997 (in/out)



300 x 600mm
53992 (in/out)



600 x 600mm
53988 (in/out)
54401 (textured 2CM)



600 x 1200mm
53983 (in/out)



300 x 300mm
53998 (in/out)



300 x 600mm
53993 (in/out)



Technical Specifications

Properties	Test Method	Required Value	Value	Applies to
 Water absorption	EN ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\%$	Full range
 Determination of dimensions	EN ISO 10545-2	Length and width $\pm 0.6\%$ Thickness $\pm 5.00\%$ Transmutation $\pm 0.5\%$	Length and width $\pm 0.1\%$ Thickness $\pm 3\%$ Transmutation $\pm 0.2\%$	Full range
 Breaking strength	EN ISO 10545-4	≥ 1300 N	≥ 1300 N	Full range
 Modulus of rupture	EN ISO 10545-4	≥ 35 N/mm ²	≥ 35 N/mm ²	Full range
 Abrasion resistance	EN ISO 10545-7	≤ 205 mm ²	≤ 160 mm ²	Full range
 Slip resistance (wet pendulum test)	AS 4586:2013	N/A	P4	Full range
 Chemical resistance	EN ISO 10545-13	Min. GB	Pass	Full range
 Stain resistance	ISO 10545-14	Min class 3	Pass	Full range
 Origin	N/A	N/A	China	Full range
 Shade variation	N/A	N/A	V2	Full range



Packing Information

Tile Description		Quantity per Box	Quantity per m2		Quantity per Pallet	
Size (mm)	Finish	Pieces	Pieces	Weight	m2	Boxes
300 x 300	In/Out	11	11.11	22.22	53.46	54
300 x 600	In/Out	8	5.56	21.52	57.60	40
600 x 600	In/Out	4	2.78	21.52	57.60	40
600 x 600 2CM Paver	Textured	2	2.78	46.53	28.80	40
600 x 1200	In/Out	2	1.39	23.26	40.32	28



The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.