

# Esla

Create seamless continuity from your internal to external spaces with this Stonework range of rustic interlocking tiles. The 440 x 600 Cobblestone and Flagstone formats are ideal for floor and wall applications. Choose from the Esla, Filita and Borgogna White colourways when creating your modern rustic aesthetic.

# Cobblestone



440 x 660mm  
53641 (textured) P5


# Flagstone



440 x 660mm  
53642 (textured) P5



# Modular



Modular (indent option available)  
53695 (textured) P5



# Stonework



440 x 660mm (indent option available)  
53696 (textured) P5

# Technical Specification

Properties	Test Method	Required Value	Value	Applies to
 Water absorption	ISO 10545-3	≤ 0.5%	0.10%	Full range
 Determination of dimensions	ISO 10545-2	Length and width 0.6% Thickness 0.5% Edge straightness 0.5% Surface flatness 0.5%	Complies with standards	Full range
 Breaking strength	ISO 10545-4	≥ 1300 N	Complies with standards	Full range
 Modulus of rupture	ISO 10545-4	≥ 35 N/mm	45.6 N/mm	Full range
 Abrasion resistance	ISO 10545-6	Max 175mm <sup>3</sup>	Complies with standards	Full range
 Slip resistance (oil wet ramp test)	DIN 51130	N/A	R12	Full range
 Slip resistance (wet pendulum test)	Wet pendulum test	N/A	P5	Full range
 Chemical resistance	ISO 10545-13	Minimum UB	Complies with standards	Full range
 Origin	N/A	N/A	Spain	Full range
 Shade variation	N/A	N/A	V2	Full range

# Packing Information

Tile description		Quantity per box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
440 x 660 Cobblestone	Textured	4	3.85	25 kg	49.92	48
440 x 660 Flagstone	Textured	4	3.85	24 kg	56.16	48
440 x 660 Modular*	Textured	6	???	?? kg	???	???
440 x 660 Stonework*	Textured	4	3.42	25 kg	49.92	48



\* Indent item

The data and information contained in these specification sheets are indicative only unless stated otherwise.  
 As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation.  
 The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose.  
 To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.  
 No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.