





**75 x 300mm (192 faces)** 53751 (in/out) P4



**300 x 300mm mosaic** 53748 (in/out) P4



**300 x 300mm (96 faces)** 53958 (in/out) P4



**300 x 600mm (48 faces)** 53705 (in/out) P4



600 x 600mm (24 faces) 53706 (in/out) P4 53709 (textured 2cm thick) P5



**398 x 600mm Coping (24 faces)** 53708 (textured) P5



**600 x 1200mm (12 faces)** 53707 (in/out) P5



**75 x 300mm (192 faces)** 53749 (in/out) P4




**300 x 300mm mosaic** 53746 (in/out) P4



**300 x 300mm (96 faces)** 53961 (in/out) P4



**300** x **600**mm **(48 faces)** 53710 (in/out) P4



600 x 600mm (24 faces) 53711 (in/out) P4 53714 (textured 2cm thick) P5



**398 x 600mm Coping (24 faces)** 53713 (textured) P5



**600 x 1200mm (12 faces)** 53712 (in/out) P4







75 x 300mm (192 faces)



300 x 300mm mosaic 53747 (in/out) P4



300 x 300mm (96 faces) 53960 (in/out) P4 53700 (in/out) P4



300 x 600mm (48 faces)



600 x 600mm (24 faces) 53701 (in/out) P4 53704 (textured 2cm thick) P5



398 x 600mm Coping (24 faces) 53703 (textured) P5



600 x 1200mm (12 faces) 53702 (in/out) P4



75 x 300mm (192 faces) 53931 (in/out) P4



300 x 300mm mosaic 53930 (in/out) P4



300 x 300mm (96 faces) 53959 (in/out) P4



300 x 600mm (48 faces) 53925 (in/out) P4



600 x 600mm (24 faces) 53927 (in/out) P4 53928 (textured 2cm thick) P5



**398 x 600mm Coping (24 faces)** 53926 (textured) P5



600 x 1200mm (12 faces) 53929 (in/out) P4



## **Technical Specification**

	Properties	Test Method	Required Value	Value	Applies to
	Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%	Full range
	Determination of dimensions	EN ISO 10545-2	Length and width ± 0.6% Thickness ± 5.00% Transmutation ± 0.5%	Length and width ± 0.1% Thickness ± 3% Transmutation ± 0.2%	Full range
	Breaking strength	EN ISO 10545-4	≥ 1300 N	≥ 1300 N	Full range
o v	Modulus of rupture	EN ISO 10545-4	≥ 35 N/mm²	≥ 35 N/mm²	Full range
(O)	Abrasion resistance	EN ISO 10545-7	≤ 205mm²	≤ 160mm²	Full range
ķ	Slip resistance (wet pendulum test)	AS 4586-2013/ AMDT1-2017	N/A	P5 P4	Textured In/out
	Chemical resistance	EN ISO 10545-13	Min. GB	Pass	Full range
	Stain resistance	ISO 10545-14	Min class 3	Pass	Full range
	Origin	N/A	N/A	China	Full range
	Shade variation	N/A	N/A	V3	Full range



## **Packing Information**

Tile description		Quantity per box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
75 x 300	In/out	36	44.44	22.22 kg	60.75	75
300 x 300	In/out	11	11.11	22.00 kg	55.44	56
300 x 300 Mosaic	In/out	11	11.11	22.22 kg	55.44	56
300 x 600	In/out	8	5.56	21.18 kg	57.60	40
398 x 600 Coping	Textured	2	4.19	46.88 kg	30.6	64
600 x 600	In/out	4	2.78	21.18 kg	57.60	40
600 x 600 2cm pavers	Textured	2	2.78	46.53 kg	28.80	40
600 x 1200	In/out	2	1.39	23.61 kg	86.40	60

The data and information contained in these specification sheets are indicative only unless stated otherwise.

As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation.

The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose.

To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.

No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

