

Tuffeau

The Tuffeau range conveys the splendor and strength of natural stone together with the versatility of porcelain stoneware. The 408 x 614mm and classic French Pattern formats are suitable for both internal and external applications, with the Bianco and Dorado colours supporting the warmth of the rustic style.



COLOURS, FORMATS & FINISHES



Matt | P2

Bianco

Dorado

408 x 614mm	●	
French Pattern	●	●

Textured | P5

408 x 614mm	●	●
French Pattern	●	●


FINISH: **MATT** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: UNRECTIFIED | V RATING: V4
FINISH: **TEXTURED** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: UNRECTIFIED | V RATING: V4



Bianco



P2 V4 P5



408 x 614mm
53576 (matt)
53577 (textured)




French Pattern
53582 (matt)
53583 (textured)

Dorado



P2 V4 P5



408 x 614mm
53579 (textured)



French Pattern
53584 (matt)
53585 (textured)

Technical Specification

Properties	Test Method	Required Value	Value	Applies to
 Water absorption	ISO 10545-3	$\leq 0.5 \%$	0,22 %	Full range
 Determination of dimensions	ISO 10545-2	Length and width $\pm 0,6\%/\pm 2.0\text{mm}$ Thickness $\pm 5\%/\pm 0.5\text{mm}$ Straightness of sides $0,5\%/\pm 1.5\text{mm}$ Rectangularity $\pm 0,5\%/\pm 2.0\text{mm}$ Surface flatness $\pm 0,5\%/\pm 2.0\text{mm}$	Compliant	Full range
 Breaking strength	ISO 10545-4	Thickness $\geq 7,5 \text{ mm}$: 1300 N min.	Compliant	Full range
 Abrasion resistance	ISO 10545-7	State the PEI rate and covered cycles.	Class 4 (2100 rotations)	Full range
 Slip resistance (wet pendulum test)	DIN 51130	N/A	P2 – Matt P5 – External	Full range
 Slip resistance (oil wet ramp test)	DIN 51130	N/A	R9 – Matt R11 – External	Full range
 Chemical resistance	ISO 10545-13	min. UB	Compliant	Full range
 Stain resistance	ISO 10545-14	Min. class 3	Class 5	Full range
 Origin	N/A	N/A	Italy	Full range
 Shade variation	N/A	N/A	V4	Full range



Packing Information

Tile Description		Quantity per Box	Quantity per m2		Quantity per Pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	Boxes
French Pattern	Matt External	6	8	20.00kg	33.00	44
408 x 614	Matt External	5	4	19.95kg	60.12	48

INSTALLATION INSTRUCTIONS

We recommend wet cutting or the score and snap method during installation. Improper installation techniques may expose installers to harmful silica dust. Do not dry cut this product using power tools during installation, as dry cutting may present a risk of serious lung injury. If adequate ventilation cannot be achieved, wear an appropriate mask or respirator. For more information, see the SDS: <https://www.coem.it/downloads/>

BOX CONTENTS

All materials are packed in one box.
Two boxes are required to complete one module.

40,8x61,4 - 16"x24"	1 pc
40,8x40,8 - 16"x16"	2 pcs
20,3x40,8 - 8"x16"	1 pc
20,3x20,3 - 8"x8"	2 pcs
Total Sqm.	0,75



The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.