

# Timeless

The Timeless range unites the elegance of Italian gold-veined Calcutta marble with the serene nuances, textures, and veins found in precious marble—beautifully replicated in the durability of porcelain tile. Visually identical to natural stone, this combined range is available in three formats: 300 × 600mm (20 faces), 600 × 600mm (10 faces), and 600 × 1200mm (8 faces), all offered in both satin and polished finishes. Suitable for interior wall and floor applications, this range creates a space that is refined, enduring, and effortlessly elegant.

# TIMELESS

## COLOURS, FORMATS & FINISHES



### Satin | P1

Gold

White

600 x 1200mm	●	●
600 x 600mm	●	●
300 x 600mm	●	●

### Polished | P1

600 x 1200mm	●	●
600 x 600mm	●	●
300 x 600mm	●	●

FINISH: **POLISHED** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V2

FINISH: **SATIN** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V2



# Gold



300 x 600mm (20 faces)  
54046 (satin)  
54047 (polished)




600 x 600mm (10 faces)  
54044 (satin)  
54045 (polished)




600 x 1200mm (8 faces)  
54042 (satin)  
54043 (polished)


# White



300 x 600mm (20 faces)  
54040 (satin)  
54041 (polished)












600 x 600mm (10 faces)  
54038 (satin)  
54039 (polished)



600 x 1200mm (8 faces)  
54036 (satin)  
54037 (polished)




# Technical Specifications

	Properties	Test Method	Required Value	Value	Applies to
	Water absorption	EN ISO 10545-3	≤ 0.5%	≤ 0.5%	Full range
	Determination of dimensions	EN ISO 10545-2	Length and width ± 0.3% Thickness ± 5.00% Transmutation ± 0.30%	Length and width ± 0.25% Thickness ± 5.00% Transmutation ± 0.30%	Full range
	Breaking strength	EN ISO 10545-4	≥ 1300 N	≥ 1300 N	Full range
	Modulus of rupture	EN ISO 10545-4	≥ 35 N/mm <sup>2</sup>	≥ 35 N/mm <sup>2</sup>	Full range
	Slip resistance (wet pendulum test)	AS 4586:2013	N/A	P1 - Satin	Full range
	Chemical resistance	EN ISO 10545-13	Min. GB	GB	Full range
	Stain resistance	EN ISO 10545-14	Min class 3	Class 3	Full range
	Origin	N/A	N/A	Malaysia	Full range
	Shade variation	N/A	N/A	V2	Full range



# Packing Information

Tile description		Quantity per box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
300 x 600	Satin Polished	8	5.56	21.40	51.84	36
600 x 600	Satin Polished	4	2.78	21.40	51.84	36
600 x 1200	Satin Polished	2	1.39	23.00	86.40	60



*The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.*

