







62.5 x 125mm (12 faces) 53954 (matt) 53953 (gloss)



125 x 125mm (6 faces) 53952 (matt) 53951 (gloss)

Technical Specification

	Properties	Test Method	Required Value	Value	Applies to
	Water absorption	ASTM C373	≤ 20.0%	≤ 16.7%	Full range
	Determination of dimensions	ASTM C499	Thickness ≤ 0.79mm	Thickness ≤ 0.5mm	Full range
	Breaking strength	ASTM C648	≥ 550 N	≥ 1340 N	Full range
0	Abrasion resistance	ASTM C1027	As reported	Class 3	Full range
	Chemical resistance	ASTM C650	Class B min.	Class A	Full range
	Origin	N/A	N/A	China	Full range
	Shade variation	N/A	N/A	N/A	Full range



Packing Information

Tile description		Quantity per box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
62.5 x 125	Matt Gloss	144	128	20.00	81.00	72
125 x 125	Matt Gloss	72	64	20.00	81.00	72



As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose.

To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet.

No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

