

Portofino



PORTOFINO

COLOURS, FORMATS & FINISHES

			
In/Out P4	Ivory	Natural	Grey
600 x 1200mm	●	●	●
600 x 1200mm Linear	●	●	●
600 x 600mm	●	●	●
300 x 600mm	●	●	●
Textured P5			
600 x 600mm 20mm Paver	●	●	●
398 x 600mm Coping Paver	●	●	●


FINISH: **IN/OUT** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V2
FINISH: **TEXTURED** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V2





V2


P4 2CM - P5




600 x 600mm
54444 (in/out)
54446 (textured 2CM)



600 x 1200mm
54445 (in/out)
54468 (linear in/out)



398 x 600mm Coping Paver
54447 (textured 2CM)




300 x 600mm
54443 (in/out)



V2


P4 2CM - P5




600 x 600mm
54450 (in/out)
54452 (textured 2CM)



600 x 1200mm
54451 (in/out)
54467 (linear in/out)




398 x 600mm Coping Paver
54453 (textured 2CM)



300 x 600mm
54449 (in/out)




Grigio




600 x 600mm
54438 (in/out)
54440 (textured 2CM)



600 x 1200mm
54439 (in/out)
54466 (linear in/out)



398 x 600mm Coving Paver
54441 (textured 2CM)



300 x 600mm
54437 (in/out)

V2
P4 2CM - P5



Technical Specifications

Properties	Test Method	Required Value	Value	Applies to
 Water absorption	ASTM C373	$\leq 0.5\%$	$\leq 0.11\%$	Full range
 Determination of dimensions	N/A	N/A	N/A	Full range
 Breaking strength	ASTM C648	≥ 1100 N	≥ 2143 N	Full range
 Abrasion resistance	ASTM C1027	As reported	Class 3	Full range
 Slip resistance (wet pendulum test)	AS 4586:2013	N/A	P4 - In/Out P5 - Textured	In/Out Textured
 Slip resistance (oil wet ramp test)	AS 4586:2013	N/A	R10	In/Out Textured
 Chemical resistance	ASTM C650	As reported	Class A	Full range
 Stain resistance	ASTM C1378	As reported	Class A	Full range
 Origin	N/A	N/A	China	Full range
 Shade variation	N/A	N/A	V2	Full range



Packing Information

Tile Description		Quantity per Box	Quantity per m2		Quantity per Pallet	
Size (mm)	Finish	Pieces	Pieces	Weight	m2	Boxes
300 x 600	In/Out	8	5.56	22.00kg	57.60	40
600 x 600	In/Out	4	2.78	22.00kg	57.60	40
600 x 600 2CM Paver	Textured	2	2.78	45.00kg	28.80	40
600 x 1200	In/Out	2	1.39	22.00kg	40.32	28
398 x 600 2CM Paver	Textured	3	3	11.50kg	25.92	36



The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.