







600 x 600mm 53762 (matt)



600 x 1200mm 53756 (matt) 53757 (polished matt) 53778 (external)





600 x 600mm 53758 (matt)



600 x 1200mm 53752 (matt) 53753 (polished matt) 53776 (external)







Technical Specification

	Properties	Test Method	Required Value	Value	Applies to
Î	Determination of dimensions	ISO 10545-2	Length and width ± 0.6% Thickness ± 5.00% Edge straightness ± 0.5% Surface flatness ± 0.5%	Compliant	Full range
	Water absorption	ISO 10545-3	≤ 0.5%	0.05%	Full range
	Breaking strength	ISO 10545-4	1300 N min.	Compliant	Full range
	Abrasion resistance	ISO 10545-6	175 mm3 max.	Compliant	Full range
· K	Slip resistance (oil wet ramp test)	DIN 51130	N/A	R10	600 x 1200 Matt
	Chemical resistance	ISO 10545-13	min. UB	Compliant	Full range
	Origin	N/A	N/A	ltaly	Full range
	Shade variation	N/A	N/A	V3	600 x 1200



Packing Information

Tile description		Quantityper box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
600 x 600*	Matt	4	2.78	30.50 kg	43.20	30
600 x 1200	Polished Matt* External	2	1.39	30.50 kg	51.84	36



The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

