

Riverwood

The Riverwood Range is inspired by the rich heritage of Mediterranean olive trees, where wood has been shaped by nature for millennia. Each 200x1200mm lath showcases a unique grain and character, bringing warmth, authenticity, and timeless appeal to any space. Designed for both indoor and outdoor applications, Riverwood is available in an In/Out finish, providing a seamless transition between spaces while ensuring durability and slip resistance.

Available in six natural tones: Fossil, Limed, Pure, Vintage, Eiger and Mocca, this collection offers a versatile palette that complements both modern and rustic aesthetics. With the ability to be laid in multiple patterns, Riverwood allows for creative installations that highlight the organic beauty of the wood grain, making it a perfect choice for residential and commercial environments.

RIVERWOOD

COLOURS, FORMATS & FINISHES



| IN/OUT P4 | Limed | Fossil | Pure | Vintage | Eiger | Mocca |
|--------------|-------|--------|------|---------|-------|-------|
| 200 x 1200mm | ● | ● | ● | ● | ● | ● |

FINISH: **IN/OUT** | CATEGORY: PORCELAIN TILES | EDGE DETAIL: RECTIFIED | V RATING: V2



Colour variation is an inherent property of all kiln-fired products. Tiles supplied may vary from samples provided. All slip ratings are provided subject to the guidelines outlined in our terms and conditions.



Limed



200 x 1200mm
54345 (in/out) P4



Fossil



200 x 1200mm
54346 (in/out) P4



Pure



200 x 1200mm
54347 (in/out) P4



Vintage



200 x 1200mm
54348 (in/out) P4



Eiger



200 x 1200mm
54349 (in/out) P4



Mocca



200 x 1200mm
54350 (in/out) P4

Technical Specification

| Properties | Test Method | Required Value | Value | Applies to |
|--|-------------------------------------|------------------------|-------------------------|------------|
|  Water absorption | EN ISO 10543-3:2018 | $E \leq 0.5\%$ | $E \leq 0.5\%$ | Full range |
|  Breaking strength | EN ISO 10545-4:2019 | $\geq 1300\text{N}$ | $\geq 1300\text{ N}$ | Full range |
|  Modulus of rupture | EN ISO 10545-4:2019 | $\geq 35\text{N/mm}^2$ | $\geq 35\text{ N/mm}^2$ | Full range |
|  Slip resistance (wet pendulum test) | AS 4586-2013/Amdt 1-2017 Appendix A | - | P4 | In/out |
|  Chemical resistance | EN ISO 10545-13:2016 | MINIMUM B | Pass | Full range |
|  Stain resistance | AS 4459.14-1999 | Min class 3 | Pass | Full range |
|  Origin | N/A | N/A | China | Full range |
|  Shade variation | N/A | N/A | V2 | Full range |

Packing Information

| Tile description | | Quantity per box | Quantity per m2 | | Quantity per pallet | |
|------------------|---------|------------------|-----------------|----------|---------------------|-------|
| Size (mm) | Texture | Pieces | Pieces | Weight | m2 | boxes |
| 200 x 1200 | In/out | 5 | 4.17 | 24.58 kg | 45.60 | 38 |



The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.